## **SPI Modified Impact Tester** (Extra Heavy-Duty)

This impact tester was developed in cooperation with the Society of the Plastics Industry (SPI) for evaluating impact resistance of rigid sheets of PVC (30-60 mils thick) and other plastics and materials exceeding the 160 inch-pounds limit of the Heavy-Duty Impact Tester (1120).

- Graduated 102 cm (40 inch) guide tube with included 8 lb weight
- Redesigned arm on the base allows the impact tester to be used in tough applications
- Stop position clamp ensures you can always test at the same height, if needed
- Optional alignment tool helps to ensure the impact tester is lined up correctly (order separately below)
- Maximum force of 320 inch-pounds with 8 lb weight
- 12.7 mm (0.500 in) diameter punch
- 16.3 mm (0.640 in) die
- Guide tube OD 44.5 mm (1.75 in), ID 39.6 mm (1.56 in)

Standards					
ASTM	D 2794, D 3029,				
	D 4226, D 5420				



SPI Heavy-Duty Impact Tester 5513

Ordering	Information
Cat. No.	Description

Cat. No.	Description
5513	SPI Heavy-Duty Impact Tester

## Comes complete with:

Basic plate; Guide tube with collar; Scale in inches-pounds, Weight (8lb); Die; Punch (Tup); Operating instructions

-								
Δ	_	•	0	c	c	0	m	c

Cat. No.	Description				
1190	Calibration Tool, for 5513				
1260	Falling Weight 8 lbs, for 5513				
1231	Lift Screw				
1220	Ball Punch 0.50 in				
5514	Anvil, 3.0 in. ID, for 5513				
1264	Die 0.64 in				
5516	Sampe Platform, for 5513				
1266	Guide Tube, for 5513				
1269	Base Plate				
1271	Arm				
1275	Base, for 5513				
1274	Stop Position Clamp, for 5513				
5515	Die Adapter, 1.25 in. ID				
5517	Anvil Kit, includes 5515 & 5516				
5519	ASTM G14 Accessory Kit*				

<sup>\*</sup>Note: G14 Accessory Kit includes a base with pipe holder, 3 lb falling weight with 5/8 inch diameter indenter.

## Technical Specifications

recrimical	Specification			
Scale	Weights	Dimensions	Net	Shipping
	included		Weight	Weight
English	3.6 kg	127 x 15 x 33 cm	16.8 kg	19.5 kg
	(8 lbs)	(50 x 6 x 13 in)	(37 lbs)	(43 lbs)

Note: Maximum sample thickness is 12.7 mm (0.5 in)

