

10 Liter Stainless Steel Open Bath System (MX10S)



Key Features

- Large, universal icon and English display
- On-screen prompts
- Single-point calibration capability

Key Specifications

Description	10 L Open Bath System
Controller Type	MX
Display	3.25" LCD
Languages Supported	English
Working Temperature Range °C	Ambient +10° to 135°
Temperature Stability °C	±0.07°
Temperature Calibration Capability	1-point
Working Access (L x W x D) (cm)	9.9 x 25.5 x 15.2 cm
Pump Type	Pressure
Flammability Class (DIN 12876-1) I (NFL)	

Common Specifications

Working Temperature Range °F	Ambient +20° to 275°
Working Temperature Range °C	Ambient +10° to 135°
Reservoir Capacity (gallons)	2.64
Reservoir Capacity (liters)	10
Reservoir/Tank Material	Stainless Steel
Reservoir Cover	Included
DuraTop	Yes
Working Access (L x W x D) (inches)	3.9 x 10.1 x 6 in
Working Access (L x W x D) (cm)	9.9 x 25.5 x 15.2 cm
Temperature Stability °F	±0.13°
Temperature Stability °C	±0.07°
Display	3.25" LCD
Display Resolution (Set)	0.1
Display Resolution (Read)	0.1
Pump Type	Pressure
Pump Speed	One
Process Connections	1/2" O.D. Barbed Tubes
Flammability Class (DIN 12876-1)	I (NFL)
Over-Temperature Protection / Failsafe Heater Control	Yes
Low Liquid Level Protection	Yes
Cooling Coil	Accessory
Maximum Ambient Temperature °F	95°
Maximum Ambient Temperature °C	35°
Overall Dimensions (L x W x H) (inches)	13.9 x 13.5 x 16 in
Overall Dimensions (L x W x H) (cm)	35.3 x 34.2 x 40.6 cm
Environmental Compliance	RoHS, WEEE
Shipping Weight (pounds)	39.0
Shipping Weight (kilograms)	17.7
Catalog Page Number	62-63

60 Hz Only

Part Number	MX10S135-A11B
Maximum Pressure (psi)	2.3
Maximum Pressure (bar)	0.16
Maximum Pressure Flow Rate (gpm)	3.60
Maximum Pressure Flow Rate (l/min)	13.5
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	120/60/1/10
Regulatory Approvals	ETL

50 Hz Only

Part Number	MX10S135-A12E
Maximum Pressure (psi)	1.8
Maximum Pressure (bar)	0.12
Maximum Pressure Flow Rate (gpm)	3.10
Maximum Pressure Flow Rate (l/min)	11.9
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	240/50/1/6
Regulatory Approvals	CE



2-170 Shield Ct
Markham, Ontario
L3R 9T5
905-475-5880