

Valueklave™ 1730

# Valueklave™ 1730



## Speed, Quality & Value

- Fast cycle time, 11 minutes from a hot start (Standard Unwrapped Cycle Time)
- Efficient drying cycle for wrapped instruments
- Contemporary design with easy to read panel
- Economically priced a compact size

# Valueklave™ 1730

The Valueklave™ 1730 will satisfy all of your basic sterilization needs at an economical price. High speed and reliability are built into every Valueklave™ 1730.



Valueklave™ 1730 Specification	
Chamber Dimensions O x L in (mm)	7"x13" (170 X 340)
Volume	2 gal/7.5 L
Overall Dimensions DxWxH in (mm)	17.9"x 17.4 "x 12" (455 x 440 x 305)
Standard Cassettes	2 half
Tray Dimensions DxWxH in (mm)	11.6"x 4.7 "x 0.8" (295 x 120 x 20)
No. of Trays	3
Standard Unwrapped Cycle Time	Cold: 16 min Hot: 11 min
Voltage (V) Freq. (Hz)	120 50/60
Power (W) Curret (A)	1350 11
Shipping Weight lbs (kg)	55 (25)

## Features:

- Fast Cycle Time. 11 minutes from a hot start\* (Standard Unwrapped Cycle time).
- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Overheat cutoff prevents burnout of heating elements in case of insufficient water in the chamber.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.



\*Come up time, sterilization exposure and exhaust



Clean&Simple™ Ultrasonic  
Cleaners and Tablets



Steam  
Distiller



Chamber Brite  
Autoclave Cleaner



## Tuttnauer USA Co., Ltd.

25 Power Drive, Hauppauge, NY 11788 Tel: +800 624 5836, +631 737 4850 Fax: +631 737 0720  
E-mail: [info@tuttnauerUSA.com](mailto:info@tuttnauerUSA.com), [www.tuttnauerUSA.com](http://www.tuttnauerUSA.com)

